

BULBS



O(ft)	H(ft)	E(fc)	O(ft)	H(ft)	E(fc)	O(ft)	H(ft)	E(fc)	O(ft)	H(ft)	E(fc)
2.79	13.1	20	2.79	13.1	35	2.79	13.1	64	2.79	13.1	75
2.10	9.8	36	2.10	9.8	62	2.10	9.8	114	2.10	9.8	134
1.38	6.6	81	1.38	6.6	139	1.38	6.6	255	1.38	6.6	302
0.69	3.3	325	0.69	3.3	557	0.69	3.3	1022	0.69	3.3	1208
12	ESX	20W	12	FMT	35W	12	EXT	50W	12	EYF	75W

O(ft)	H(ft)	E(fc)	O(ft)	H(ft)	E(fc)	O(ft)	H(ft)	E(fc)	O(ft)	H(ft)	E(fc)
5.58	13.1	7	5.58	13.1	13	5.58	13.1	21	5.58	13.1	28
4.20	9.8	12	4.20	9.8	24	4.20	9.8	37	4.20	9.8	50
2.79	6.6	28	2.79	6.6	53	2.79	6.6	84	2.79	6.6	111
1.41	3.3	111	1.41	3.3	214	1.41	3.3	334	1.41	3.3	446
24	BBF	20W	24	FMV	35W	24	EXZ	50W	24	EYJ	75W

O(ft)	H(ft)	E(fc)	O(ft)	H(ft)	E(fc)	O(ft)	H(ft)	E(fc)	O(ft)	H(ft)	E(fc)
8.53	13.1	4	8.53	13.1	8	8.53	13.1	12	8.53	13.1	16
6.40	9.8	6	6.40	9.8	13	6.40	9.8	21	6.40	9.8	28
4.26	6.6	14	4.26	6.6	30	4.26	6.6	46	4.26	6.6	63
2.13	3.3	56	2.13	3.3	121	2.13	3.3	186	2.13	3.3	251
36	BAB	20W	36	FMW	35W	36	EXN	50W	36	EYC	75W

O(ft)	H(ft)	E(fc)	O(ft)	H(ft)	E(fc)	O(ft)	H(ft)	E(fc)	O(ft)	H(ft)	E(fc)
15.15	13.1	2	15.15	13.1	3	15.15	13.1	5	15.15	13.1	7
11.35	9.8	3	11.35	9.8	5	11.35	9.8	9	11.35	9.8	13
7.58	6.6	6	7.58	6.6	12	7.58	6.6	20	7.58	6.6	28
3.77	3.3	25	3.77	3.3	47	3.77	3.3	79	3.77	3.3	113
60	BAB/60	20W	60	FMW/60	35W	60	FNV	50W	60	EYC/60	75W

POPSTAR SERIES / A

AVAILABLE IN: Red, Orange, Yellow, Green, Blue and Magenta

- 4000 hours average life
- Integrated dichroic colored front glass cover
- Dimmable
- UV protection
- Cool beam

MR-8 BULB / B

AVAILABLE IN: 5W, 10W, 20W or 35W with 30° degree beam spread

- 1 inch Diameter
- 2000 hours average life
- Integrated cover glass
- Precisely focused light cone
- Dimmable

MR-16 BULB / D

AVAILABLE IN:

- 10W 36"
- 20W 12", 24", 36", 60"
- 35W 12", 24", 36", 60"
- 50W 12", 24", 36", 60"
- 75W 12", 36", 60"

- Long Life- up to 4000 hours average
- Excellent center-to-edge uniformity
- High quality Titanium Oxide coating
- Axial filament for precise beam control
- Auto-resettable in-line primary overload protection
- Dimmable
- Crisp white Halogen light
- UV-cut Halogen capsule



MR-11 BULB / C

AVAILABLE IN: 20W 30", (NFL) or 10" (NSP) beam spreads

- No light diffusion from back-spill
- Reduced heat to socket, fixture and transformers
- Axial filament for precise beam control
- Dimmable
- Crisp white Halogen light
- UV-cut Halogen capsule
- Flush fitting integral front glass

PAR 20 / E

AVAILABLE IN: 39W spot or flood

Metal Halide lamp is constructed of an outer glass bulb with an internal arc-tube. Only operate with compatible ballast and fixture. Metal Halide arc-tubes operate at high pressure and at very high temperatures.

PAR36 BULB / F

AVAILABLE IN: 20w 32", 36w 13" or 32" or 50w 13" (special order)

- 4000 hour average life
- Screw terminal

BI-PINS / G

AVAILABLE IN: G4: 5W, 10W, or 20W or GY6.35: 20W, 35W or 50W

- Approved for use in open luminaires
- Standard Bi-Pin
- Clear finish
- 4000 hour average rated life
- Axial filament for optimum directional light
- Special pins for corrosion protection
- Color temperature 3000K